

C.2 Text accents

Name	Type	Typeset	Name	Type	Typeset
acute	<code>\' {o}</code>	ó	macron	<code>\={o}</code>	ō
breve	<code>\u{o}</code>	ö	overdot	<code>\.{g}</code>	ġ
caron/haček	<code>\v{o}</code>	ě	ring	<code>\r{u}</code>	û
cedilla	<code>\c{c}</code>	ç	tie	<code>\t{oo}</code>	ôo
circumflex	<code>\^ {o}</code>	ô	tilde	<code>\~ {n}</code>	ñ
dieresis/umlaut	<code>\" {u}</code>	ü	underdot	<code>\d{m}</code>	ṁ
double acute	<code>\H{o}</code>	ő	underbar	<code>\b{o}</code>	ḡ
grave	<code>\' {o}</code>	ò			
dotless i	<code>\i</code>	ı	dotless j	<code>\j</code>	ĵ
	<code>\' {\i}</code>	í		<code>\v {\j}</code>	ĵ

C.3 Text font commands

C.3.1 Text font family commands

Command with Argument	Command Declaration	Switches to the font family
<code>\textnormal{...}</code>	<code>{\normalfont ...}</code>	document
<code>\emph{...}</code>	<code>{\em ...}</code>	<i>emphasis</i>
<code>\textrm{...}</code>	<code>{\rmfamily ...}</code>	roman
<code>\textsf{...}</code>	<code>{\sffamily ...}</code>	sans serif
<code>\texttt{...}</code>	<code>{\ttfamily ...}</code>	typewriter style
<code>\textup{...}</code>	<code>{\upshape ...}</code>	upright shape
<code>\textit{...}</code>	<code>{\itshape ...}</code>	<i>italic shape</i>
<code>\textsl{...}</code>	<code>{\slshape ...}</code>	<i>slanted shape</i>
<code>\textsc{...}</code>	<code>{\scshape ...}</code>	SMALL CAPITALS
<code>\textbf{...}</code>	<code>{\bfseries ...}</code>	bold
<code>\textmd{...}</code>	<code>{\mdseries ...}</code>	normal weight and width